

# Sea Tel<sup>®</sup> 2406 Ku-Band TX/RX

*When the going gets rough, Sea Tel<sup>®</sup> keeps going*



**The 2406 Antenna** is a 60 cm Ku-Band maritime VSAT antenna for SCPC, broadband, or hybrid networks. This antenna system complies with the FCC's 04-286, WRC-03 resolution 902 and ETSI's latest EN 320 420 for ESV (Earth Stations on Vessels), which is a remarkable achievement for a 60 cm ring-focus antenna. Although small the antenna is still built to Sea Tel's exacting standards for vibration, shock and EMC. The antenna efficiency is better than 70% across the transmit and receive bands and is ideal for vessels that require "always-on" broadband satellite communications. The 2406 is suitable for file and image transfer, video conferencing, e-mail, Virtual Private Networks (VPNs), and database backup.

**COBHAM** Antennas

[www.seatel.com](http://www.seatel.com)

**Sea Tel<sup>®</sup>**  
*Look to the Leader. Look to Sea Tel.*

## Communications

- Antenna: 0.6 m/24 " ring focus
- Radome: .87m/34" D x 1m/39" H
- Weight: 113 Kg/ 250lbs
- Feed Assembly: Orthogonal Linear polarized
- Transmit Gain: 36 dB mid band
- Receive Gain: 34 dB mid band
- Roll/Pitch Amplitude: +/- 25 degree roll, +/- 15 degree pitch
- Pedestal Type: 3-axis: Level, Cross Level and Azimuth
- Rate (all axis): 90 degrees/second
- Acceleration (all axis): 60 degrees/second<sup>2</sup>
- Stabilization Accuracy: +/- 0.2 degrees under the following conditions
- Tangential Accelerations: 0.5 G in 6 seconds
- Azimuth Stabilization: Requires heading reference signal from ship's gyrocompass system.
- Operating Temperature Range: -20 to +55 Degrees C
- System G/T calculated includes radome and receive filter: 13.5 dB/k min
- Cross-Pole Isolation: >30 dB
- Sidelobes: Meets FCC EIRP Spectral Density Mask @ -20 dBW / 4 KHz
- 1-year parts; 1-year labor

Marine Electronics Croatia – Tel: +385-51-880272 – Fax: +385-51-880273 – E-mail: [sales@navcom-solutions.com](mailto:sales@navcom-solutions.com)